ЗАКАЗАТЬ: NH3/MR-1000 сенсор аммиака 0-1000 ppm

SPECIFICATION SHEET FOR NH3 SENSOR TYPE NH3/MR-1000

PERFORMANCE CHARACTERISTICS

Nominal Range	0 – 1000 ppm
Maximum Overload	ND
Expected Operation Life	2 years in air
Output Signal	25 ± 8 nA/ppm
Resolution	4 ppm
Temperature Range	- 10 ℃ to 50 ℃
Pressure Range	Atmospheric [1)]
Pressure Coefficient	No data
T_{90} Response Time	< 35 sec
Relative Humidity Range	15 % to 90 % R.H. non-condensing
Typical Baseline Range (pure air, 20℃)	0 ppm +/- 16 ppm
Maximum Zero Shift (+20℃ to +40℃)	ND
Expected Long Term Output Drift	< 5 % signal loss per 6 month
Recommended Load Resistor	10 - 20 Ohm
Bias Voltage	Not allowed
Repeatability	< 3 % of signal
Output Linearity	< 5 % full scale
Humidity Effect	< 16 ppm

CROSS-SENSITIVITY DATA

Interfering Gas	Concentration	Reading
CO	300 ppm	0 ppm
H_2	200 ppm	0 ppm
SO_2 [3)]	20 ppm	-7 ppm
H_2S [3)]	20 ppm	7 ppm
NO [3)]	20 ppm	-1 ppm
NO_2 [3)]	20 ppm	-20 ppm
Cl_2	20 ppm	-55 ppm
CO2	2 %	0 ppm

[3)] Long term exposures and high concentrations may affect the performance characteristics

Performance data conditions:
20 ℃, 50% RH and 1013 mbar

APPLICATIONS

Safety and Environmental Control
For Portable Gas Detectors

PHYSICAL CHARACTERISTICS

Weight	~ 5.4 g
Position Sensitivity	None
Storage Life	Six months in container
Recommended Storage Temperature	5 ℃ – 20 ℃
Warranty Period	12 months from date of dispatch

Miniature-Size Outline Dimensions

BOTTOM VIEW



SIDE VIEW



The data contained in this document is for guidance only. Membrapor AG accepts no liability for any consequential losses, injury or damage resulting from the use of this document or the information contained within it. The data is given for guidance only. Customers should test under their own conditions, to ensure that the sensors are suitable for their own requirements.

Phone: +41 43 311 72 00
Fax : +41 43 311 72 01

MEMBRAPOR AG
Birkernweg 2
CH-8304 Wallisellen
Switzerland

ЗАКАЗАТЬ: NH3/MR-1000 сенсор аммиака 0-1000 ppm